

Technische Daten: NGE-Ausführung

NGE	DN	PN	L (mm)	Gewicht: ca. (kg)
50-16	50	10/16	230	15
65-16	65	10/16	290	20
80-16	80	10/16	310	25
100-16	100	10/16	350	40
125-16	125	10/16	400	60
150-16	150	10/16	480	70
200-16	200	10/16	600	120
250-16	250	10/16	730	190
300-16	300	10/16	850	350
350-16	350	10/16	980	540
400-16	400	10/16	1100	620
450-16	450	10/16	1200	650
500-16	500	10/16	1250	980
600-16	600	10/16	1450	1080

Technische Daten: GE-Ausführung

GE	DN	PN	L (mm)	Gewicht: ca. (kg)	*)
32-16	32	10/16	215	13	1)
40-16	40	10/16	215	13	1)
50-16	50	10/16	254	20	1)
65-16	65	10/16	280	25	1)
80-16	80	10/16	305	30	1)
100-16	100	10/16	381	50	1)
150-16	150	10/16	508	95	1)
200-16	200	10/16	645	170	1)
250-16	250	10/16	756	310	1)
300-16	300	10/16	864	470	1)
400-16	400	10/16	1051	970	1)
600-16	600	10/16	1450	1950	1)

KCOS = Standardausführung Regelventile:
 KC: Epoxid-Pulverbeschichtung (Minimum 250 µm)
 KO: Deckelschrauben aus Edelstahl
 KS: Sitz und Gegensitz aus Edelstahl

1) In Eckausführung lieferbar. Auf Anfrage

